


THE 1/4" DIAMETER HOLE REQUIRED TO ACCESS THE ADJUSTABLE BOLT WILL NO LONGER BE REQUIRED. OUR NEW SPRING LOADED ADJUSTABLE BOLT GUIDE WILL ALLOW ADJUSTMENT OF BOTH TOP & BOTTOM BOLT WITHOUT REMOVAL OF THE DOOR. THE BOLTS CAN BE ADJUSTED SIMPLY BY ROTATING THE BOLTS AS REQ'D. USING THE THIN PROFILE HEX WRENCH PROVIDED, OR ANY 1/2" OPEN END WRENCH.

ACCESS HOLE ON STILE NO LONGER REQUIRED.

DIMENSIONAL TOLERANCES UNLESS OTHERWISE SPECIFIED DECIMAL DIMENSIONS .XX ± .010 DECIMAL DIMENSIONS .XXX ± .005 ANGULAR ± ° FRACTIONAL ± 1/64		APPROVALS APPROVED CHECKED DRAWN R.M. 9/16/97	DATE  9/16/97	 3447 UNION PACIFIC AVE. LOS ANGELES, CALIF. 90023
FILE NO. NEXT ASSY. QTY. USED 1	MATERIAL FINISH HEAT TREAT	SCALE NONE	SHEET 1 OF 1 SHEETS DWG. NO. 10-878 REV. A	
PRODUCT NOTICE FOR NEW BOLT GUIDE (TYP. FOR TOP & BTM BOLT GUIDES)				