



TRIM MTG. SCREWS
1/4-20 X 2 3/8" FHMS
(2 PLCS)

MTG. HOLES 2175 PANIC
AND 7500LVDT TRIM.
SEE DWG. 10-686 FOR
COMPLETE INSTALLATION
OF 2175 PANIC

LOCATION OF ϕ
PER DWG. 10-686.

DRILL "F" (.257 DIA.)
THRU BOTH WALLS
(2 PLCS)

6-5/16"

35" FROM BTM
OF DOOR

PANIC SIDE (INSIDE)
ACTIVE STILE

TRIM SIDE (OUTSIDE)
ACTIVE STILE

7500LVDT DUMMY OUTSIDE TRIM W/LEVER

LEVER TRIM IS NON-HANDED
REVERSABLE BY REMOVING
ATTACHMENT SCREW AND
REPOSITIONING LEVER AND
RETIGHTENING ATTACHMENT SCREW.

DIMENSIONAL TOLERANCES UNLESS OTHERWISE SPECIFIED	APPROVALS	DATE
DECIMAL DIMENSIONS .XX ± .010	APPROVED	
DECIMAL DIMENSIONS .XXX ± .005	CHECKED	
ANGULAR ± ° FRACTIONAL ± 1/64	DRAWN	M.G. 03/29/94
MATERIAL	SCALE	NONE



Jackson
EXIT DEVICE

3447 UNION PACIFIC AVE.
LOS ANGELES, CALIF. 90023

NEXT ASSY.	FINISH
QTY. USED	HEAT TREAT

7500LVDT DUMMY
LEVER TRIM

SHEET 1 OF 2 SHEETS	REV.
DWG. NO.	
10-802	