



WHEN USING ACTIVE TRIM USE GUIDE NO. 10-997

1/4" FINISH WASHER
2 PLACES
10-24 x 2-1/8 FHMS
2 PLACES

1275 PANIC

LOCATION OF ϕ
PER DWG. 10-1082

MTG. POINTS 1275 PANIC AND 7500LV TRIM SEE DWG. 10-1082 FOR COMPLETE INSTALLATION OF 1275 PANIC

ϕ 1-21/32

40" FROM BTM OF DOOR

PANIC SIDE (INSIDE)
ACTIVE STILE

TRIM SIDE (OUTSIDE)
ACTIVE STILE

7500LV-02 OUTSIDE TRIM (SHOWN)
WITH FLAT LEVER

DIMENSIONAL TOLERANCES UNLESS OTHERWISE SPECIFIED		APPROVALS	DATE
DECIMAL DIMENSIONS .XX ± .010		APPROVED	
DECIMAL DIMENSIONS .XXX ± .005		CHECKED	
ANGULAR ± ° FRACTIONAL ± 1/64		DRAWN	R.M. 03/05/01
MATERIAL		SCALE	NONE

Jackson
CORPORATION
3447 UNION PACIFIC AVE.
LOS ANGELES, CALIF. 90023

NEXT ASSY.	FINISH	7500LV-01/02 SER. INST. GUIDE	SHEET 1 OF 1 SHEETS	
QTY. USED	HEAT TREAT		DWG. NO. 10-1090	REV. A